

DebianRedHat64Linux

Google ChromeFirefoxEdgeIE10HTML5
IE

1.

1		8G50G	Tomcat
2		8G50G	Tomcat
		8G100G	MongoDB+Redis
NAS		100G	2 /app_home
Nginx		4G50G	

2.

<http://pan.macochart.com/index.php/s/HpDortYC5bNgyKC>

2

- (1) maco-platform-xxx.tar.gz
- (2) maco-datacache-xxx.tar.gz

3.

<http://pan.macochart.com/index.php/s/8CMZTNJesfCCJ5M>

1war

- (1) maco-clientmode-x.x.x.war

4.

- (1) maco-datacache-xxx.tar.gz /opt/maco-datacache-xxx.tar.gz
- (2)

```
cd /opt
tar xvfz maco-datacache-xxx.tar.gz
```

- (3) MongoDB

```
cd /opt/maco/mongodb
./run.sh
```

(4) Redis

```
cd /opt/maco/redis
./run.sh
```

5. 1

```
/var/tmp
mkdir /app_home/var_tmp
rm -fr /var/tmp
ln -s /app_home/var_tmp /var/tmp
```

(1) maco-platform-xxx.tar.gz 1 /opt/maco-platform-xxx.tar.gz

(2)

```
cd /opt
tar xvfz maco-platform-xxx.tar.gz
```

(3) /opt/maco/app_home/conf/system.properties

```
app_home=/app_home
```

(4) /app_home/conf/db.properties

```
#IPMongoDBx.x.x.xIP
platform.mongodb.host=x.x.x.x
platform.mongodb.port=27017
```

(5) /app_home/conf/redis.properties

```
#IPRedisx.x.x.xIP
redis.host=x.x.x.x
redis.port=6379
```

(6) Tomcat

```
cd /opt/maco
./run.sh
```

(7) :

```
cd /opt/maco  
./taillog.sh
```

(8)
<http://x.x.x.x:9090> x.x.x.x

6. 1

- Linux

7. 2

(1) maco-platform-xxx.tar.gz 2 /opt/maco-platform-xxx.tar.gz
(2)

```
cd /opt  
tar xvfz maco-platform-xxx.tar.gz
```

(3) /opt/maco/app_home/conf/system.properties

```
app_home=/app_home
```

(4) Tomcat

```
cd /opt/maco  
./run.sh
```

(5) :

```
cd /opt/maco  
./taillog.sh
```

(6)
<http://x.x.x.x:9090> x.x.x.x

8. 2

- Linux

9. Nginx

```

upstream platform_server {
    server x.x.x.x:9090;
    server y.y.y.y:9090;
}

server {
    listen      80;
    server_name mbi.xxx.com;
    autoindex off;
    index index.do;
    charset utf-8;
    client_max_body_size 300M;

    location ~ / {
        proxy_read_timeout 3600;
        proxy_connect_timeout 3600;
        proxy_pass http://platform_server;
        proxy_redirect off;
        proxy_set_header    Host
$host;
        proxy_set_header    X-Real-IP
$remote_addr;
        proxy_set_header    X-Forwarded-For
$proxy_add_x_forwarded_for;
        proxy_set_header X-Forwarded-Proto
$scheme;
        proxy_http_version 1.1;
        proxy_set_header Upgrade
$http_upgrade;
        proxy_set_header Connection "upgrade";

    }
}

```

1. x.x.x.x:9090 1IPTomcat9090
2. y.y.y.y:9090 2IPTomcat9090
3. mbi.xxx.com