

- Windows

	100	300
2G-4G CPU 50-100G	8G-16G CPU 300G	32 CPU 500G

50G

Windows Server 2008 64
Win7Win8Win8.1Win10 64

Google ChromeFirefoxEdgeIE10HTML5
IE

Windows

1.

<https://pan.macochart.com/s/tKGEyGnaFd3BGDi>

<https://pan.macochart.com/s/czFdonTFoo4JNXi>

2. d:\macoDmacoD

D:\maco				
名称	修改日期	类型	大小	
app	2018/12/6 15:14	文件夹		
app_home	2019/7/10 10:21	文件夹		
bin	2018/12/6 15:14	文件夹		
jdk1.7	2018/12/6 15:14	文件夹		
maco.war	2019/6/17 13:19	文件夹		
mongodb	2018/12/6 15:15	文件夹		
tomcat8	2019/7/11 12:22	文件夹		
控件发布	2019/7/10 10:29	文件夹		
D3控件_20190704	2019/7/4 8:27	HTML 文件	109 KB	

3.

D:\maco\tomcat8\conf\server.xml

```
62 <!-- A "Connector" represents an endpoint by which requests are received
63 and responses are returned. Documentation at :
64 Java HTTP Connector: /docs/config/http.html (blocking & non-blocking)
65 Java AJP Connector: /docs/config/ajp.html
66 APR (HTTP/AJP) Connector: /docs/apr.html
67 Define a non-SSL HTTP/1.1 Connector on port 8080
68 -->
69 <Connector port="8080" protocol="HTTP/1.1"
70     connectionTimeout="20000"
71     maxPostSize="2000000"
72     maxHttpHeaderSize="200000"
73     redirectPort="8443" />
74 <!-- A "Connector" using the shared thread pool-->
75 <!--
76 <Connector executor="tomcatThreadPool"
77     port="8080" protocol="HTTP/1.1"
78     connectionTimeout="20000"
79     redirectPort="8443" />
80 -->
81 <!-- Define a SSL HTTP/1.1 Connector on port 8443
82 This connector uses the NIO implementation that requires the JSSE
83 style configuration. When using the APR/native implementation, the
84 OpenSSL style configuration is required as described in the APR/native
```

4. bin
5. : install
6. run 30
7. http://127.0.0.1:
- 8.

更新许可证

服务器ID: 0d804e4711b66886c3f0cc848b6b92c

许可证文件: 请选择许可证文件

选择文件

1. admin/password
2. ->

